

fax

TO	FAX NUMBER	PHONE NUMBER
U.S. PATENT & TRADEMARK OFFICE EXAMINER J. HEWITT	571-273-7084	
SENDER	SENDER'S FAX NUMBER	SENDER'S PHONE NUMBER
Ryan M. Flandro	202-344-8300	202-344-4221
	SENDER'S ACTING ASSISTANT	ASSISTANT'S PHONE NUMBER
	Susan Brockmeyer	202-344-4025
DATE	CLIENT/MATTER NUMBER	PAGES, INCLUDING COVER
September 15, 2010	32128-227053	2

MESSAGE

**PROPOSED AMENDMENTS TO THE CLAIMS
U.S. Patent Application No. 10/563,249**

If you require assistance with this transmission, please contact the sender.

This message is intended only for the use of the individual or entity to which it is addressed and may contain information that is privileged, confidential, and exempt from disclosure under applicable law. If the reader of this message is not the intended recipient or the employee or agent responsible for delivering the message to the intended recipient, you are hereby notified that any dissemination, distribution, or copying of this communication is strictly prohibited. If you have received this communication in error, please notify us immediately by telephone and return the original message to us at the above address via the U.S. postal service.

U.S. Treasury Circular 230 Notice: Any tax advice contained in this facsimile transmission (including the cover sheet), unless otherwise stated, was not intended or written to be used, and cannot be used, for the purpose of (a) avoiding tax-related penalties; or (b) promoting, marketing or recommending to another party any tax-related matter addressed herein. We provide this disclosure on all faxes to ensure compliance with new standards of professional practice, pursuant to which certain tax advice must meet requirements as to form and substance. Thank you.

#1129128v1

PROPOSED AMENDMENTS TO THE CLAIMS

***** FOR DISCUSSION PURPOSES ONLY – NOT FOR ENTRY *****

1. *(Currently Amended)* A connector seal device for connecting a branch pipe to a transverse opening of a main pipe, the connector seal device comprising:
 - a hollow elastomer insert composed in part of a first material, the elastomer insert including:
 - a flexible support collar; and
 - a sealing wall region with an inside surface tapered in an insertion direction and having first locking ring zones and an outside surface adapted to fit a diameter of the transverse opening, wherein the first locking ring zones comprise a first plurality of ring-shaped teeth and ring-shaped grooves defining a saw-tooth shaped cross section; and
 - ~~an outside surface adapted to fit a diameter of the transverse opening;~~
 - a pipe union of a second material, the second material being harder than the first material, the pipe union including:
 - an engagement end with an outside surface tapered in the insertion direction and being adapted to cooperate with the inside surface of the elastomer insert, the outside surface having second locking ring zones comprising a second plurality of ring-shaped teeth and ring-shaped grooves defining a saw-tooth shaped cross section and being adapted to cooperate with the inside surface of the elastomer insert; and
 - a socket end adapted to cooperate with the branch pipe,
- whereby when the elastomer insert is inserted in the insertion direction into the transverse opening and the pipe union is ~~inserted~~ pushed in the insertion direction into the elastomer insert, the first and second locking ring zones engage in the manner of ratchet teeth and the elastomer insert is expanded and pressed further against the transverse opening through the continued displacement of the pipe union in the insertion direction.